



# Material Safety Data Sheet

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know.

This MSDS covers the following Aerove aerosol product.

**PRODUCT NAME:** 1690 Asphalt Roof Primer

## SECTION I - MANUFACTURER IDENTIFICATION

**MANUFACTURER'S NAME:** Aerove Industries Inc.  
**INFORMATION PHONE:** 775-782-0100  
**DATE REVISED:** November 19, 2008

**ADDRESS:** 1198 Mark Circle, Gardnerville, NV 89410  
**EMERGENCY PHONE:** 1-800-424-9300  
**REASON REVISED:** Updated

## SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
Petroleum Asphalt (8052-42-4)	30 - 60	N / AV	N / AV	N / AV	N / AV
Aliphatic Hydrocarbon (CAS 8052-41-3)	10 - 30	500 ppm	100 ppm	N / AV	N / AV
Hydrocarbon Propellant (CAS 68476-86-8)	10 - 30	1000 ppm	1000 ppm	N / AV	N / AV
Aliphatic Petroleum Distillates (CAS 64742-89-8)	5 - 10	N / AV	300 ppm	N / AV	N / AV
Aromatic Petroleum Distillates (CAS 64742-95-6)	5 - 10	N / AV	N / AV	N / AV	N / AV

\*\*\*No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.\*\*\*

**NOTE:** N / AP = Not Applicable N / AV = Not Available

1690MA

## SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

**BOILING POINT:** N / AP  
**VAPOR DENSITY:** Heavier than air  
**EVAPORATION RATE:** Slower than n-Butyl Acetate

**SPECIFIC GRAVITY (H20=1):** 0.8  
**SOLUBILITY IN WATER:** Negligible  
**APPEARANCE AND ODOR:** Black liquid with hydrocarbon odor

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT:** < 0° F (-18° C) **METHOD USED:** Estimated **FLAMMABLE LIMITS - LEL:** 0.7% **UEL:** 9.5%  
**EXTINGUISHING MEDIA:** Carbon dioxide, dry chemical, water spray.  
**SPECIAL FIRE FIGHTING PROCEDURES:** Use water spray to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.  
**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Treat as cylinders of compressed gas. Closed containers may rupture due to pressure build up from extreme temperature.  
**FLAMMABILITY:** Flammable aerosol under conditions of sparks, flame, or hot surfaces.  
**SENSITIVITY TO IMPACT:** Aerosol cans are under pressure. Product will be expelled rapidly if container is punctured.  
**SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors

## SECTION V - REACTIVITY DATA

**STABILITY:** Stable **CONDITIONS TO AVOID:** Open flames, sparks, electrical arcs.  
**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents.  
**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Carbon Monoxide, Carbon Dioxide.  
**HAZARDOUS POLYMERIZATION:** Will not occur

## SECTION VI - HEALTH HAZARD DATA

**INHALATION:** Respiratory tract irritant. May cause dizziness, light-headedness and / or headaches.  
**SKIN CONTACT:** Prolonged or repeated contact may cause irritation and dermatitis.  
**EYE CONTACT:** Painful with slight to moderate irritation.  
**SKIN ABSORPTION:** Not likely to be absorbed in toxic amounts under normal use.  
**INGESTION:** Not likely to be harmful in small amounts but swallowing large amounts may be harmful.  
**CARCINOGENICITY:** The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.  
**TERATOGENICITY:** Not established **MUTAGENICITY:** Not established  
**MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE:** Not established  
**EMERGENCY AND FIRST AID PROCEDURES:** INHALATION - Remove from exposure, seek medical attention if signs/symptoms persist.  
 SKIN - Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.  
 EYES - Flush immediately with water for 15 minutes, seek medical attention if irritation persists.  
 INGESTION - Do NOT induce vomiting, drink plenty of water, seek medical attention.

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.  
**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.  
**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Do not store above 120° F (49° C). Do not store or use near heat, sparks or flame.  
**OTHER PRECAUTIONS:** Do not smoke while using this product.

## SECTION VIII - CONTROL MEASURES

**RESPIRATORY PROTECTION:** In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator. For concentrations above the TLV (as defined in Section II), use a positive air supplied respirator.  
**VENTILATION:** General ventilation to maintain exposure limits below TLV's as defined in Section II.  
**PROTECTIVE GLOVES:** Chemical resistant gloves such as Neoprene or Nitrile rubber.  
**EYE PROTECTION:** Safety glasses or goggles.  
**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Not established.  
**WORK / HYGIENIC PRACTICES:** Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

## SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.