



SECTION 1 - Product Information

Product Identifier: 7007 Cold Galvanizing Coating 93% Zinc Rich**Product Use:** Galvanizing Paint**Manufacturer's Name:** AerVOE Industries Inc.**Address:** 1100 Mark Circle, Gardnerville, NV 89410**Emergency Phone:** 1-800-424-9300**Preparation Date:** June 6, 2010

SECTION 2 - Hazardous Ingredients

Hazardous Ingredients	Weight %	CAS Number	LD ₅₀ of Ingredient (species & route)	LC ₅₀ of Ingredient (species)
Zinc	30 - 60	7440-66-6	N / AV	N / AV
Hydrocarbon Propellant	10 - 30	68476-86-8	N / AV	N / AV
VM & P Naphtha	10 - 30	64742-89-8	> 2.84 g / kg (Rat-Dermal)	15,000 ppm / 4 hr (Rat)
Methyl Ethyl Ketone	5 - 10	78-93-3	N / AV	N / AV

SECTION 3 - Physical Data

Physical State: Aerosol**Specific Gravity:** 1.4**Evaporation Rate:** Faster than n-Butyl Acetate**Boiling Point:** N / AP**Freezing Point:** N / AV**pH:** N / AP**Vapor Density (air = 1):** Heavier than air**Vapor Pressure (psig):** 45 to 55**Odor and Appearance:** Aromatic odor / Metallic gray liquid

SECTION 4 - Fire and Explosion Data

Flammability: Flammable aerosol under conditions of sparks, flame, or excessive heat.**Means of Extinction:** *Extinguishing Media* - Carbon dioxide, dry chemical, water spray. *Firefighting Procedures* - Treat as cylinders of compressed gas. Closed containers may rupture due to pressure build up from extreme temperature. Use water spray to cool containers to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.**Flashpoint:** < 0° F (-18° C)**Method Used:** Estimated**Flammable Limits - LFL:** 0.9% **UFL:** 11.5%**Autoignition Temperature:** N / AV**Hazardous Combustion Products:** Carbon Monoxide, Carbon Dioxide.**Explosion Data - Sensitivity to Mechanical Impact:** No**Explosion Data - Sensitivity to Static Discharge:** No

SECTION 5 - Reactivity Data

Chemical Stability: Stable**Incompatibility with Other Substances:** Strong oxidizing agents, strong acids or bases.**Reactivity & Conditions:** None**Hazardous Decomposition Products:** None**Primary Routes of Entry:** Skin Contact, Eye Contact, Inhalation**Effects of Acute Exposure to Product:***Skin Contact* - Irritation.*Eye Contact* - Irritation.*Inhalation* - Irritation. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.**Effects of Chronic Exposure to Product:** Dermatitis. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood.**Exposure Limits (TLV):**

Zinc N / AV - ACGIH 2005

Hydrocarbon Propellant N / AV - ACGIH 2005

Aliphatic Petroleum Distillates N / AV - ACGIH 2005

Methyl Ethyl Ketone 200 ppm TWA and 300 ppm STEL - ACGIH 2005

Irritancy: Skin, eyes, and respiratory tract.**Sensitization:** N / AV**Carcinogenicity:** The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.**Reproductive Toxicity:** N / AV**Teratogenicity:** N / AV**Mutagenicity:** N / AV**Synergistic Products:** N / AV

SECTION 7 - Preventive Measures

Personal Protective Equipment (PPE): Gloves - Yes Respirator - Yes Eye - Yes Footwear - No Clothing - No Other - No*Skin Protection* - Chemical resistant gloves such as Neoprene or Nitrile rubber.*Respiratory Protection* - In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator.

For concentrations above the TLV (as defined in Section 6), use a positive air supplied respirator.

Eye Protection - Safety glasses or goggles.**Engineering Controls:** General ventilation to maintain exposure limits below TLV's as defined in Section 6.**Leak and Spill Procedure:** Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.**Waste Disposal:** Dispose of in accordance with local, state/provincial or territorial, and federal regulations. Do not incinerate closed containers.**Handling Procedures and Equipment:** Do not use near heat, sparks, or open flame. Use PPE as defined in Section 7.**Storage Requirements:** Do not store near heat, sparks, flame or above 120° F (49° C).**Special Shipping Information:** Consumer Commodity ORM-D.

SECTION 8 - First Aid Measures

Inhalation: Remove from exposure, seek medical attention if signs/symptoms persist.**Ingestion:** Do not induce vomiting. Contact physician or poison control center immediately.**Skin Contact:** Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.**Eye Contact:** Flush immediately with water for 15 minutes, seek medical attention if irritation persists.

SECTION 9 - Preparation Information

Prepared by: Technical Department**Telephone Number:** 775-783-3100**Preparation Date:** June 2, 2010

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.