



SECTION 1 - Product Information

Product Identifier: 7007 Cold Galvanizing Compound
Product Use: Galvanizing Paint
Manufacturer's Name: AerVOE Industries Inc.
Address: 1198 Mark Circle, Gardnerville, NV 89410
Emergency Phone: 1-800-424-9300
Preparation Date: June 19, 2008

SECTION 2 - Hazardous Ingredients

Hazardous Ingredients	Weight %	CAS Number	LD ₅₀ of Ingredient (species & route)	LC ₅₀ of Ingredient (species)
Zinc	30 - 60	7440-66-6	N / AV	N / AV
Hydrocarbon Propellant	10 - 30	68476-86-8	N / AV	N / AV
VM & P Naphtha	10 - 30	64742-89-8	> 2.84 g / kg (Rat-Dermal)	15,000 ppm / 4 hr (Rat)
Methyl Ethyl Ketone	5 - 10	78-93-3	N / AV	N / AV

SECTION 3 - Physical Data

Physical State: Aerosol
Boiling Point: N / AP
Vapor Density (air = 1): Heavier than air
Odor and Appearance: Aromatic odor / Metallic gray liquid

Specific Gravity: 1.4
Freezing Point: N / AV
Vapor Pressure (psig): 45 to 55

Evaporation Rate: Faster than n-Butyl Acetate
pH: N / AP

SECTION 4 - Fire and Explosion Data

Flammability: Flammable aerosol under conditions of sparks, flame, or excessive heat.
Means of Extinction: *Extinguishing Media* - Carbon dioxide, dry chemical, water spray. *Firefighting Procedures* - Treat as cylinders of compressed gas. Closed containers may rupture due to pressure build up from extreme temperature. Use water spray to cool containers to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.
Flashpoint: < 0° F (-18° C) **Method Used:** Estimated **Flammable Limits - LFL:** 0.9% **UFL:** 11.5%
Autoignition Temperature: N / AV **Hazardous Combustion Products:** Carbon Monoxide, Carbon Dioxide.
Explosion Data - Sensitivity to Mechanical Impact: No **Explosion Data - Sensitivity to Static Discharge:** No

SECTION 5 - Reactivity Data

Chemical Stability: Stable
Reactivity & Conditions: None

Incompatibility with Other Substances: Strong oxidizing agents, strong acids or bases.
Hazardous Decomposition Products: None

NOTE: N / AP = Not Applicable N / AV = Not Available

SECTION 6 - Toxicological Properties

Primary Routes of Entry: Skin Contact, Eye Contact, Inhalation

Effects of Acute Exposure to Product:

Skin Contact - Irritation.

Eye Contact - Irritation.

Inhalation - Irritation. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Effects of Chronic Exposure to Product: Dermatitis. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood.

Exposure Limits (TLV):

Zinc N / AV - ACGIH 2005

Hydrocarbon Propellant N / AV - ACGIH 2005

Aliphatic Petroleum Distillates N / AV - ACGIH 2005

Methyl Ethyl Ketone 200 ppm TWA and 300 ppm STEL - ACGIH 2005

Irritancy: Skin, eyes, and respiratory tract.

Sensitization: N / AV

Carcinogenicity: The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive Toxicity: N / AV **Teratogenicity:** N / AV **Mutagenicity:** N / AV **Synergistic Products:** N / AV

SECTION 7 - Preventive Measures

Personal Protective Equipment (PPE): Gloves - Yes Respirator - Yes Eye - Yes Footwear - No Clothing - No Other - No

Skin Protection - Chemical resistant gloves such as Neoprene or Nitrile rubber.

Respiratory Protection - In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator.

For concentrations above the TLV (as defined in Section 6), use a positive air supplied respirator.

Eye Protection - Safety glasses or goggles.

Engineering Controls: General ventilation to maintain exposure limits below TLV's as defined in Section 6.

Leak and Spill Procedure: Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.

Waste Disposal: Dispose of in accordance with local, state/provincial or territorial, and federal regulations. Do not incinerate closed containers.

Handling Procedures and Equipment: Do not use near heat, sparks, or open flame. Use PPE as defined in Section 7.

Storage Requirements: Do not store near heat, sparks, flame or above 120° F (49° C).

Special Shipping Information: Consumer Commodity ORM-D.

SECTION 8 - First Aid Measures

Inhalation: Remove from exposure, seek medical attention if signs/symptoms persist.

Ingestion: Do not induce vomiting. Contact physician or poison control center immediately.

Skin Contact: Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.

Eye Contact: Flush immediately with water for 15 minutes, seek medical attention if irritation persists.

SECTION 9 - Preparation Information

Prepared by: Technical Department

Telephone Number: 775-782-0100

Preparation Date: June 19, 2008

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.