



## SECTION 1 - Product Information

Product Identifier: 2811 Tan Stencil Cover Up

Product Use: Cover-up Ink

Manufacturer's Name: Aerove Industries Inc.

Address: 1100 Mark Circle, Gardnerville, NV 89410

Emergency Phone: 1-800-424-9300

Preparation Date: March 2, 2011

## SECTION 2 - Hazardous Ingredients

Hazardous Ingredients	Weight %	CAS Number	LD <sub>50</sub> of Ingredient (species & route)	LC <sub>50</sub> of Ingredient (species)
Acetone	15 - 40	67-64-1	5800 mg / kg (Rat-Oral)	21000 ppm / 8 hr (Rat)
Hydrocarbon Propellant	10 - 30	68476-86-8	N / AV	N / AV
Aliphatic Petroleum Distillates	5 - 10	64742-89-8	> 2.84 g / kg (Rat-Dermal)	15,000 ppm / 4 hr (Rat)
Methyl Ethyl Ketone	3 - 7	78-93-3	N / AV	N / AV
n-Butyl Acetate	1 - 5	123-86-4	N / AV	N / AV

## SECTION 3 - Physical Data

Physical State: Aerosol      Specific Gravity: 0.8      Evaporation Rate: Faster than n-Butyl Acetate  
Boiling Point: N / AP      Freezing Point: N / AV      pH: N / AP  
Vapor Density (air = 1): Heavier than air      Vapor Pressure (psig): 45 to 55  
Odor and Appearance: Ketone odor / Opaque liquid

## SECTION 4 - Fire and Explosion Data

Flammability: Yes - Flammable aerosol under conditions of sparks, flame, or excessive heat.

Means of Extinction: *Extinguishing Media* - Carbon dioxide, dry chemical, water spray. *Firefighting Procedures* - Treat as cylinders of compressed gas. Closed containers may rupture due to pressure build up from extreme temperature. Use water spray to cool containers to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.

Flashpoint: &lt; 0° F (-18° C)      Method Used: Estimated      Flammable Limits - LFL: 0.7%      UFL: 12.8%

Autoignition Temperature: N / AV      Hazardous Combustion Products: Carbon Monoxide, Carbon Dioxide.

Explosion Data - Sensitivity to Mechanical Impact: No      Explosion Data - Sensitivity to Static Discharge: No

## SECTION 5 - Reactivity Data

Chemical Stability: Stable      Incompatibility with Other Substances: Strong oxidizing agents.  
Reactivity & Conditions: None      Hazardous Decomposition Products: None

NOTE: N / AP = Not Applicable      N / AV = Not Available

Primary Routes of Entry: Skin Contact, Eye Contact, Inhalation

Effects of Acute Exposure to Product:

*Skin Contact* - Irritation.*Eye Contact* - Irritation.*Inhalation* - Irritation. May cause dizziness, light-headedness and / or headaches.

Effects of Chronic Exposure to Product: Dermatitis.

Exposure Limits (TLV):

Acetone      500 ppm TWA and 750 ppm STEL - ACGIH 2005

Hydrocarbon Propellant      N / AV - ACGIH 2005

Aliphatic Petroleum Distillates      N / AV - ACGIH 2005

Methyl Ethyl Ketone      200 ppm TWA and 300 ppm STEL - ACGIH 2005

n-Butyl Acetate      150 ppm TWA and 200 ppm STEL - ACGIH 2005

Irritancy: Skin, eyes, and respiratory tract.

Sensitization: N / AV

Carcinogenicity: The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive Toxicity: N / AV      Teratogenicity: N / AV      Mutagenicity: N / AV      Synergistic Products: N / AV

## SECTION 7 - Preventive Measures

Personal Protective Equipment (PPE): Gloves - Yes      Respirator - Yes      Eye - Yes      Footwear - No      Clothing - No      Other - No  
*Skin Protection* - Chemical resistant gloves such as Neoprene or Nitrile rubber.*Respiratory Protection* - In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator.

For concentrations above the TLV (as defined in Section 6), use a positive air supplied respirator.

*Eye Protection* - Safety glasses or goggles.**Engineering Controls:** General ventilation to maintain exposure limits below TLV's as defined in Section 6.**Leak and Spill Procedure:** Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.**Waste Disposal:** Dispose of in accordance with local, state/provincial or territorial, and federal regulations. Do not incinerate closed containers.**Handling Procedures and Equipment:** Do not use near heat, sparks, or open flame. Use PPE as defined in Section 7.**Storage Requirements:** Do not store near heat, sparks, flame or above 120° F (49° C).**Special Shipping Information:** Consumer Commodity ORM-D.

## SECTION 8 - First Aid Measures

**Inhalation:** Remove from exposure, seek medical attention if signs/symptoms persist.**Ingestion:** Do NOT induce vomiting, seek medical attention.**Skin Contact:** Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.**Eye Contact:** Flush immediately with water for 15 minutes, seek medical attention if irritation persists.

## SECTION 9 - Preparation Information

Prepared by: Technical Department

Telephone Number: 775-783-3100

Preparation Date: 3-2-2011

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.