



SECTION 1 - Product Information

Product Identifier:

Non-Fluorescent Colors		Fluorescent Colors		16 oz. I.A.C.		High Delivery		Metallic	
201 Red	207 White	220 Red	261 Red	270 Fluorescent Red	281 Red	210 Silver			
202 Yellow	208 Hi Visibility Yellow	222 Orange	262 Yellow	272 Fluorescent Orange	282 Yellow				
203 Blue	209 Light Blue	224 Green	263 Blue	274 Fluorescent Green	288 Fluorescent Orange				
204 Green	212 Purple	226 Yellow	265 Orange	275 Fluorescent Red/Orange					
205 Orange		227 Blue	267 White	279 Fluorescent Pink					
206 Black		229 Pink							
		230 Red/Orange							

Product Use: Ground Marking Paint
Manufacturer's Name: Aerove Industries Inc.
Address: 1100 Mark Circle, Gardnerville, NV 89410
Emergency Phone: 1-800-424-9300
Preparation Date: April 23, 2010

SECTION 2 - Hazardous Ingredients

Hazardous Ingredients	Weight %	CAS Number	LD ₅₀ of Ingredient (species & route)	LC ₅₀ of Ingredient (species)
Aliphatic Petroleum Distillates	10 - 30	64742-89-8	> 2.84 g / kg (Rat-Dermal)	15,000 ppm / 4 hr (Rat)
Propane	7 - 13	74-98-6	N / AV	N / AV
Hexane	7 - 13	110-54-3	2870 mg / kg (Rat-Oral)	N / AV
Aliphatic Petroleum Distillates	1 - 5	64742-88-7	N / AV	N / AV
n-Butane	1 - 5	106-97-8	N / AV	N / AV
Isobutane	1 - 5	75-28-5	N / AV	57 pph / 15 min (Rat)
Non-Fluorescent Colors Also Contain:				
Acetone	1 - 5	67-64-1	5800 mg / kg (Rat-Oral)	21000 ppm / 8 hr (Rat)
Metallic Colors Also Contain:				
Acetone	30 - 60	67-64-1	5800 mg / kg (Rat-Oral)	21000 ppm / 8 hr (Rat)
n-Butyl Acetate	1 - 5	123-86-4	N / AV	N / AV
Aliphatic Hydrocarbon	1 - 5	64742-47-8	N / AV	N / AV

NOTE: N / AP = Not Applicable N / AV = Not Available

C17A

Survey Marking Paint SECTION 3 - Physical Data

Physical State: Aerosol
Boiling Point: N / AP
Vapor Density (air = 1): Heavier than air
Odor Threshold (ppm): N / AV
Specific Gravity: 0.9
Freezing Point: N / AV
Vapor Pressure (psig): 35 to 55
Coefficient of Water/Oil Distribution: N / AV
Evaporation Rate: Faster than n-Butyl Acetate
pH: N / AP
Odor and Appearance: Hydrocarbon odor / Opaque liquid

SECTION 4 - Fire and Explosion Data

Flammability: Flammable aerosol under conditions of sparks, flame, or excessive heat.
Means of Extinction: *Extinguishing Media* - Carbon dioxide, dry chemical, water spray. *Firefighting Procedures* - Treat as cylinders of compressed gas. Closed containers may rupture due to pressure build up from extreme temperature. Use water spray to cool containers to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.
Flashpoint: < 0° F (-18° C)
Autoignition Temperature: N / AV
Explosion Data - Sensitivity to Mechanical Impact: No
Method Used: Estimated
Hazardous Combustion Products: Carbon Monoxide, Carbon Dioxide.
Explosion Data - Sensitivity to Static Discharge: No
Flammable Limits - LFL: 0.9% **UFL:** 13.0%

SECTION 5 - Reactivity Data

Chemical Stability: Stable
Reactivity & Conditions: None
Incompatibility with Other Substances: Strong oxidizing agents.
Hazardous Decomposition Products: None

SECTION 6 - Toxicological Properties

Primary Routes of Entry: Skin Contact, Eye Contact, Inhalation
Effects of Acute Exposure to Product:
Skin Contact - Irritation. *Eye Contact* - Irritation.
Inhalation - Irritation. May cause dizziness, light-headedness and / or headaches. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
Effects of Chronic Exposure to Product: Dermatitis. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood.

Exposure Limits (TLV):

Aliphatic Hydrocarbon	100 ppm TWA - ACGIH 2005
Aliphatic Petroleum Distillates	N / AV - ACGIH 2005
Propane	2500 ppm TWA - ACGIH 2005
Hexane	50 ppm TWA (Skin) - ACGIH 2005
Acetone	500 ppm TWA and 750 ppm STEL - ACGIH 2005
n-Butyl Acetate	150 ppm TWA and 200 ppm STEL - ACGIH 2005
n-Butane	800 ppm TWA - ACGIH 2005
Isobutane	N / AV - ACGIH 2005

Irritancy: Skin, eyes, and respiratory tract. **Sensitization:** N / AV
Carcinogenicity: The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA. **Reproductive Toxicity:** N / AV
Teratogenicity: N / AV
Mutagenicity: N / AV
Synergistic Products: N / AV

SECTION 7 - Preventive Measures

Personal Protective Equipment (PPE): Gloves - Yes Respirator - Yes Eye - Yes Footwear - No Clothing - No Other - No
Skin Protection - Chemical resistant gloves such as Neoprene or Nitrile rubber.
Respiratory Protection - In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator. For concentrations above the TLV (as defined in Section 6), use a positive air supplied respirator.
Eye Protection - Safety glasses or goggles.
Engineering Controls: General ventilation to maintain exposure limits below TLV's as defined in Section 6.
Leak and Spill Procedure: Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse.
Waste Disposal: Dispose of in accordance with local, state/provincial or territorial, and federal regulations. Do not incinerate closed containers.
Handling Procedures and Equipment: Do not use near heat, sparks, or open flame. Use PPE as defined in Section 7.
Storage Requirements: Do not store near heat, sparks, flame or above 120° F (49° C).
Special Shipping Information: Consumer Commodity ORM-D.

SECTION 8 - First Aid Measures

Inhalation: Remove from exposure, seek medical attention if signs/symptoms persist.
Ingestion: Do not induce vomiting. Contact physician or poison control center immediately.
Skin Contact: Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.
Eye Contact: Flush immediately with water for 15 minutes, seek medical attention if irritation persists.

SECTION 9 - Preparation Information

Prepared by: Technical Department **Telephone Number:** 775-783-3100 **Preparation Date:** 04-23-10
 THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO.
 NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.