



SECTION 1 - Product Information

Product Identifier: Zynolyte Multi-Purpose Primer

Z8070 Dark Gray	Z8077 Green
Z8072 Gray	Z8078 Black
Z8074 Red Oxide	Z8079 Yellow
Z8076 White	

Product Use: Primer Paint

Manufacturer's Name: Aervoe Industries Inc.

Address: 1100 Mark Circle, Gardnerville, NV 89410

Emergency Phone: 1-800-424-9300

Preparation Date: February 15, 2011

SECTION 2 - Hazardous Ingredients

Hazardous Ingredients	Weight %	CAS Number	LD ₅₀ of Ingredient (species & route)	LC ₅₀ of Ingredient (species)
Propane	10 - 20	74-98-6	N / AV	N / AV
Acetone	10 - 20	67-64-1	5800 mg / kg (Rat-Oral)	21000 ppm / 8 hr (Rat)
n-Butyl Acetate	5 - 10	123-86-4	N / AV	N / AV
n-Butane	3 - 7	106-97-8	N / AV	N / AV
Aliphatic Petroleum Distillates	1 - 5	64742-89-8	N / AV	N / AV
Isobutane	1 - 5	75-28-5	N / AV	57 pph / 15 min (Rat)

SECTION 3 - Physical Data

Physical State: Aerosol	Specific Gravity: 0.9	Evaporation Rate: Faster than n-Butyl Acetate
Boiling Point: N / AP	Freezing Point: N / AV	pH: N / AP
Vapor Density (air = 1): Heavier than air		Vapor Pressure (psig):
Odor and Appearance: Opaque with a hydrocarbon odor		Odor Threshold (ppm): N / AV
Coefficient of Water/Oil Distribution: N / AV		

SECTION 4 - Fire and Explosion Data

Flammability: Yes - Flammable aerosol under conditions of sparks, flame, or excessive heat.

Means of Extinction: *Extinguishing Media* - Carbon dioxide, foam, dry chemical. *Firefighting Procedures* - Treat as cylinders of compressed gas. Closed containers may rupture due to pressure build up from extreme temperature. Use water spray to cool containers to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.

Flashpoint: < 0° F (-18° C) Method Used: Estimated Flammable Limits - LFL: 1.0% UFL: 15.0%

Autoignition Temperature: N / AV Hazardous Combustion Products: Carbon Monoxide, Carbon Dioxide.

Explosion Data - Sensitivity to Mechanical Impact: No Explosion Data - Sensitivity to Static Discharge: No

SECTION 5 - Reactivity Data

Chemical Stability: Stable	Incompatibility with Other Substances: Strong oxidizing agents.
Reactivity & Conditions: None	Hazardous Decomposition Products: None

NOTE: N / AP = Not Applicable N / AV = Not Available

SECTION 6 - Toxicological Properties

Primary Routes of Entry: Skin Contact, Eye Contact, Inhalation

Effects of Acute Exposure to Product:

Skin Contact - Irritation.*Eye Contact* - Irritation.*Inhalation* - Irritation. May cause dizziness, light-headedness and / or headaches.

Effects of Chronic Exposure to Product: Dermatitis.

Exposure Limits (TLV):

Acetone	500 ppm TWA and 750 ppm STEL - ACGIH 2005
Propane	2500 ppm TWA - ACGIH 2005
n-Butyl Acetate	150 ppm TWA and 200 ppm STEL - ACGIH 2005
n-Butane	800 ppm TWA - ACGIH 2005
Aliphatic Petroleum Distillates	N / AV - ACGIH 2005
Isobutane	N / AV - ACGIH 2005

Irritancy: Skin, eyes, and respiratory tract.

Sensitization: N / AV

Carcinogenicity: The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive Toxicity: N / AV Teratogenicity: N / AV Mutagenicity: N / AV Synergistic Products: N / AV

SECTION 7 - Preventive Measures

Personal Protective Equipment (PPE): Gloves - Yes Respirator - Yes Eye - Yes Footwear - No Clothing - No Other - No
Skin Protection - Chemical resistant gloves such as Neoprene or Nitrile rubber.*Respiratory Protection* - In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator.

For concentrations above the TLV (as defined in Section 6), use a positive air supplied respirator.

Eye Protection - Safety glasses or goggles.**Engineering Controls:** General ventilation to maintain exposure limits below TLV's as defined in Section 6.**Leak and Spill Procedure:** Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.**Waste Disposal:** Dispose of in accordance with local, state/provincial or territorial, and federal regulations. Do not incinerate closed containers.**Handling Procedures and Equipment:** Do not use near heat, sparks, or open flame. Use PPE as defined in Section 7.**Storage Requirements:** Do not store near heat, sparks, flame or above 120° F (49° C).**Special Shipping Information:** Consumer Commodity ORM-D.

SECTION 8 - First Aid Measures

Inhalation: Remove from exposure, seek medical attention if signs/symptoms persist.**Ingestion:** Do NOT induce vomiting, drink plenty of water, seek medical attention.**Skin Contact:** Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.**Eye Contact:** Flush immediately with water for 15 minutes, seek medical attention if irritation persists.

SECTION 9 - Preparation Information

Prepared by: Technical Department

Telephone Number: 775-783-3100

Preparation Date: 2-15-2011

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.