



# Material Safety Data Sheet

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know.

As per 29 CFR 1900. 1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following Aerove aerosol products.

**PRODUCT NAME:** Supreme Color Shield Paint

5004 Safety Blue	5010 Safety Orange	5016 Flat Black
5005 Light Blue	5011 Equipment Orange	5017 Black
5006 Safety Green	5012 Safety Red	5018 Flat White
5007 Hunter Green	5013 Brite Red	5019 White
5008 Safety Yellow	5014 Sand	5020 Light Gray (ANSI - 61)
5009 Equipment Yellow	5015 Brown	5049 Meter Gray (ANS I- 49)
		5050 Padmount Green

**SECTION I - MANUFACTURER IDENTIFICATION**

**MANUFACTURER'S NAME:** Aerove Industries, Inc.  
**INFORMATION PHONE:** 775-782-0100  
**DATE REVISED:** January 3, 2008

**ADDRESS:** 1198 Mark Circle, Gardnerville, NV 89410  
**EMERGENCY PHONE:** 1-800-424-9300  
**REASON REVISED:** New

**SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION  
 OCCUPATIONAL EXPOSURE LIMITS**

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	ACGIH STEL	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
Acetone (CAS 67-64-1)	15 - 40	1000 ppm	500 ppm		5800 mg / kg (Rat-Oral)	21000 ppm / 8 hr (Rat-Inha)
Hydrocarbon Propellant (CAS 68476-86-8)	10 - 30	1000 ppm	1000 ppm		N / AV	N / AV
Aliphatic Hydrocarbon (CAS 3032-32-4)	5 - 10	300 ppm	300 ppm		N / AV	N / AV
Dipropylene Glycol Methyl Ether (CAS 34590-94-8)	1 - 5	100 ppm (skin)	100 ppm (skin)	150 ppm	N / AV	N / AV
Aliphatic Petroleum Distillates (CAS 64742-89-8)	1 - 5	N / AV	300 ppm		N / AV	N / AV
<b>5016, 5018 &amp; 5019 also contains:</b> Aliphatic Hydrocarbon (CAS 8052-41-3)	.5 - 1.5	500 ppm	100 ppm		N / AV	N / AV

\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

**NOTE:** N / AP = Not Applicable N / AV = Not Available

5004MA

**SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS**

**BOILING POINT:** N/A  
**VAPOR DENSITY:** Heavier than air  
**EVAPORATION RATE:** Faster than n-Butyl Acetate  
**SPECIFIC GRAVITY (H20=1):** 0.7 to 0.8  
**SOLUBILITY IN WATER:** Partially  
**APPEARANCE AND ODOR:** Opaque liquid with ketone odor.

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

**FLASH POINT:** < 0° F (-18° C) **METHOD USED:** Estimated **FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER:** 0.7% **UPPER:** 12.8%  
**EXTINGUISHING MEDIA:** CO<sub>2</sub>, Dry Chemical, Water Spray  
**SPECIAL FIRE FIGHTING PROCEDURES:** Use water spray to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.  
**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Treat as cylinders of compressed gas. Closed containers may rupture due to pressure build up from extreme heat or fire.  
**FLAMMABILITY:** Flammable aerosol under conditions of sparks, flame, or hot surfaces.  
**SENSITIVITY TO IMPACT:** Product will be expelled rapidly if container is punctured  
**SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors

**SECTION V - REACTIVITY DATA**

**STABILITY:** Stable **CONDITIONS TO AVOID:** Open flames, sparks, electrical arcs.  
**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents.  
**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Carbon Dioxide, Carbon Monoxide  
**HAZARDOUS POLYMERIZATION:** Will not occur

**SECTION VI - HEALTH HAZARD DATA**

**INHALATION:** Respiratory tract irritant. May cause dizziness, light-headedness and / or headaches.  
**SKIN CONTACT:** Prolonged or repeated contact may cause irritation and dermatitis.  
**EYE CONTACT:** Painful with slight to moderate irritation.  
**SKIN ABSORPTION:** Not likely to be absorbed in toxic amounts under normal use.  
**INGESTION:** Not likely in normal use but swallowing large amounts may be harmful.  
**CARCINOGENICITY:** The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.  
**TERATOGENICITY:** Not established **MUTAGENICITY:** Not established  
**MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE:** Not established  
**EMERGENCY AND FIRST AID PROCEDURES:** INHALATION - Remove from exposure, seek medical attention if signs/symptoms persist.  
 SKIN - Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.  
 EYES - Flush immediately with water for 15 minutes, seek medical attention if irritation persists.  
 INGESTION - Do NOT induce vomiting, drink plenty of water, seek medical attention if irritation persists.

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.  
**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.  
**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Do not store above 120° F (49°C). Do not store or use near heat, sparks or flame.  
**OTHER PRECAUTIONS:** Do not smoke while using this product. Dust from sanding the dry paint film should be treated as a nuisance dust with a TLV of 15 mg / cubic meter.

**SECTION VIII - CONTROL MEASURES**

**RESPIRATORY PROTECTION:** In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator. For concentrations above the TLV (as defined in Section II), use a positive air supplied respirator.  
**VENTILATION:** General ventilation to maintain exposure limits below TLV's as defined in Section II.  
**PROTECTIVE GLOVES:** Chemical resistant gloves such as Neoprene or Nitrile rubber.  
**EYE PROTECTION:** Safety glasses or goggles.  
**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** None  
**WORK / HYGIENIC PRACTICES:** Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

**SECTION IX - DISCLAIMER**

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.