



Material Safety Data Sheet

TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

This MSDS covers the following Aerove bulk product.

PRODUCT NAME: Aerove Survey Marking Paint:

207 White

208 HI Vis Yellow

SECTION I - MANUFACTURER IDENTIFICATION**MANUFACTURER'S NAME:** Aerove Industries Inc.**INFORMATION PHONE:** 775-783-3100**DATE REVISED:** January 18, 2012**ADDRESS:** 1100 Mark Circle, Gardnerville, NV 89410**EMERGENCY PHONE:** 1-800-424-9300**REASON REVISED:** Updated**SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION
OCCUPATIONAL EXPOSURE LIMITS**

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	OTHER	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
n-Butyl Acetate (CAS 123-86-4)	10 - 30	150 ppm	150 ppm		N / AV	N / AV
Aliphatic Hydrocarbon (CAS 8052-41-3)	3 - 7	500 ppm	100 ppm		N / AV	N / AV
*Glycol Ether EB Acetate (CAS 112-07-2)	1 - 5	N / AV	N / AV		N / AV	N / AV

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

NOTE: N/A applies to not available or not applicable**SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS****BOILING POINT:** 149° to 289° F (65° to 142.8° C)**ODOR THRESHOLD:** N/A**EVAPORATION RATE:** Slower than n-Butyl Acetate**COATING V.O.C. :** 6.24 lbs / Imp gal**SPECIFIC GRAVITY (H2O=1):** 1.1**VAPOR DENSITY:** Heavier than air**APPEARANCE AND ODOR:** Opaque Liquid / Solvent Based Odor

5.2 lbs / US gal

523 gms / ltr

COEFFICIENT OF WATER/OIL DIST: N/A**SOLUBILITY IN WATER:** Negligible**FREEZING POINT:** N/A**pH:** N/A**SECTION IV - FIRE AND EXPLOSION HAZARD DATA****FLASH POINT:** 59° to 74° F (15° to 23.3° C)**FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER:** .7%**EXTINGUISHING MEDIA:** Foam, Alcohol Foam, CO₂, Dry Chemical, Water Fog**SPECIAL FIRE FIGHTING PROCEDURES:** Water spray may be ineffective, but water spray may be used to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may rupture due to pressure build up from extreme heat or fire.**FLAMMABILITY:** Yes - Flammable liquid under conditions of sparks, flame, or hot surfaces.**SENSITIVITY TO IMPACT:** Do not puncture**SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors**SECTION V - REACTIVITY DATA****STABILITY:** Stable**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Carbon Monoxide and Carbon Dioxide**HAZARDOUS POLYMERIZATION:** Will not occur**SECTION VI - HEALTH HAZARD DATA****INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause dizziness or nausea.**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** SKIN - May cause irritation or burning sensation.**EYES -** Primary irritation.**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause irritation or burning sensation.**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** N/A**HEALTH HAZARDS (ACUTE AND CHRONIC):** INHALATION - Anesthetic. Irritation of the respiratory tract, or nervous system depression (characterized by headache, dizziness, nausea or possible unconsciousness). SKIN OR EYE CONTACT - Primary irritation. Prolonged or repeated contact to skin may cause dermatitis - exercise due care.**CARCINOGENICITY:** None known**NTP? No****IARC MONOGRAPHS? No****OSHA REGULATED? No****TERATOGENICITY:** N/A**MUTAGENICITY:** N/A**TOXICOLOGICALLY SYNERGISTIC PRODUCT:** N/A**MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE:** None known**EMERGENCY AND FIRST AID PROCEDURES:** VAPORS - Remove from exposure and restore breathing, seek medical attention.**SPLASH - (SKIN)** Wash affected area, remove contaminated clothing, see physician if any irritation persists.**SPLASH - (EYES)** Flush immediately with water for 15 minutes and take to a physician.**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition - Flames, sparks, static electricity & electrical. Ventilate area, avoid run off into sewer by diking, and soak up with inert absorbent using non-sparking type tools.**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Do not store above 120° F (49° C). Do not store or use near heat, sparks or flame.**OTHER PRECAUTIONS:** Do not get in eyes. Do not breathe vapors. Avoid skin contact. Do not take internally. Smoking while using this product must be strictly prohibited. In addition to all other hazards and precautions - dust from sanding the dry paint films should be treated as a nuisance dust with a TLV of 10mg/cubic meter.**SECTION VIII - CONTROL MEASURES****RESPIRATORY PROTECTION:** Outdoors - Recommend an approved mechanical particulate filter to remove any airborne overspray. In restricted areas with poor ventilation, use a NIOSH approved Organic Cartridge Respirator. For concentrations above the exposure limit, use a positive air supplied respirator.**VENTILATION:** All application areas should be adequately ventilated in order to keep the items in SECTION II below their exposure limits.**PROTECTIVE GLOVES:** Impervious gloves (natural rubber) are recommended to prevent skin contact.**EYE PROTECTION:** Safety glasses with side shields are recommended to prevent eye contact.**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Impervious apron (natural rubber) is recommended to prevent skin contact. Eye wash fountain and safety shower.**WORK / HYGIENIC PRACTICES:** Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.**SECTION IX - DISCLAIMER**

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.



Material Safety Data Sheet

TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

This MSDS covers the following Aervoe bulk product.

PRODUCT NAME: Aervoe Survey Marking Paint**Fluorescent Colors**

220 Red
222 Orange
227 Blue
229 Pink
230 Red/Orange

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Aervoe Industries Inc.
INFORMATION PHONE: 775-783-3100
DATE REVISED: January 18, 2012

ADDRESS: 1100 Mark Circle, Gardnerville, NV 89410
EMERGENCY PHONE: 1-800-424-9300
REASON REVISED: Updated

**SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION
OCCUPATIONAL EXPOSURE LIMITS**

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	OTHER	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
Aliphatic Petroleum Distillates (CAS 64742-89-8)	15 - 40	N / AV	300 ppm		N / AV	N / AV
Aliphatic Hydrocarbon (CAS 8032-32-4)	5 - 10	300 ppm	300 ppm		N / AV	N / AV
*Glycol Ether EB Acetate (CAS 112-07-2)	1 - 5	N / AV	N / AV		N / AV	N / AV

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

NOTE: N/A applies to not available or not applicable

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS
BOILING POINT: 185° F **SPECIFIC GRAVITY (H20=1):** 1.2 **COEFFICIENT OF WATER/OIL DIST:** N/A
ODOR THRESHOLD: N/A **VAPOR DENSITY:** Heavier than air **SOLUBILITY IN WATER:** Negligible
EVAPORATION RATE: Slower than n-Butyl Acetate **APPEARANCE AND ODOR:** Opaque Liquid / Solvent Based Odor
FREEZING POINT: N/A **pH:** N/A

SECTION IV - FIRE AND EXPLOSION HAZARD DATA
FLASH POINT: 50° F (10° C) **METHOD USED:** Estimated **FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER:** 1.3% **UPPER:** 8.0%
EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO₂, Dry Chemical, Water Fog
SPECIAL FIRE FIGHTING PROCEDURES: Water spray may be ineffective, but water spray may be used to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may rupture due to pressure build up from extreme heat or fire.
FLAMMABILITY: Yes - Flammable liquid under conditions of sparks, flame, or hot surfaces.
SENSITIVITY TO IMPACT: Do not puncture **SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors

SECTION V - REACTIVITY DATA
STABILITY: Stable **CONDITIONS TO AVOID:** High temperatures
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Monoxide and Carbon Dioxide
HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - HEALTH HAZARD DATA
INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: May cause dizziness or nausea.
SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: SKIN - May cause irritation or burning sensation.
EYES - Primary irritation.
SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: May cause irritation or burning sensation.
INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: N/A
HEALTH HAZARDS (ACUTE AND CHRONIC): INHALATION - Anesthetic. Irritation of the respiratory tract, or nervous system depression (characterized by headache, dizziness, nausea or possible unconsciousness). SKIN OR EYE CONTACT - Primary irritation. Prolonged or repeated contact to skin may cause dermatitis - exercise due care.
CARCINOGENICITY: None known **NTP?** No **IARC MONOGRAPHS?** No **OSHA REGULATED?** No
TERATOGENICITY: N/A **MUTAGENICITY:** N/A **TOXICOLOGICALLY SYNERGISTIC PRODUCT:** N/A
MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE: None known
EMERGENCY AND FIRST AID PROCEDURES: VAPORS - Remove from exposure and restore breathing, seek medical attention.
SPLASH - (SKIN) Wash affected area, remove contaminated clothing, see physician if any irritation persists.
SPLASH - (EYES) Flush immediately with water for 15 minutes and take to a physician.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition - Flames, sparks, static electricity & electrical. Ventilate area, avoid run off into sewer by diking, and soak up with inert absorbent using non-sparking type tools.
WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120° F (49° C). Do not store or use near heat, sparks or flame.
OTHER PRECAUTIONS: Do not get in eyes. Do not breathe vapors. Avoid skin contact. Do not take internally. Smoking while using this product must be strictly prohibited. In addition to all other hazards and precautions - dust from sanding the dry paint films should be treated as a nuisance dust with a TLV of 10mg/cubic meter.

SECTION VIII - CONTROL MEASURES
RESPIRATORY PROTECTION: Outdoors - Recommend an approved mechanical particulate filter to remove any airborne overspray. In restricted areas with poor ventilation, use a NIOSH approved Organic Cartridge Respirator. For concentrations above the exposure limit, use a positive air supplied respirator.
VENTILATION: All application areas should be adequately ventilated in order to keep the items in SECTION II below their exposure limits.
PROTECTIVE GLOVES: Impervious gloves (natural rubber) are recommended to prevent skin contact.
EYE PROTECTION: Safety glasses with side shields are recommended to prevent eye contact.
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Impervious apron (natural rubber) is recommended to prevent skin contact. Eye wash fountain and safety shower.
WORK / HYGIENIC PRACTICES: Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

SECTION IX - DISCLAIMER
 THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.