



SECTION 1 - Product Information

Product Identifier:

Tree Marking Paint - Regular Colors

610 Red	645 Dark Green
620 Orange	650 Blue
630 Yellow	660 Black
640 Green	670 White
	681 Purple

Product Use: Tree Marking Paint

Manufacturer's Name: Aerove Industries Inc.

Address: 1198 Mark Circle, Gardnerville, NV 89410

Emergency Phone: 1-800-424-9300

Preparation Date: January 12, 2010

SECTION 2 - Hazardous Ingredients

Hazardous Ingredients	Weight %	CAS Number	LD ₅₀ of Ingredient (species & route)	LC ₅₀ of Ingredient (species)
Aliphatic Hydrocarbon	40 - 70	8052-41-3	N / AV	N / AV
Isopropanol	1 - 5	67-63-0	4700 mg / kg (Rat-Oral)	16000 ppm / 4 hr (Rat-Inha)

SECTION 3 - Physical Data

Physical State: Liquid
Boiling Point: 340° to 400° (171° to 204° C)
Vapor Density (air = 1): Heavier than air
Odor and Appearance: Hydrocarbon odor / Opaque liquid
Coefficient of Water/Oil Distribution: N / AV

Specific Gravity: 0.9 to 1.0

Freezing Point: N / AV

Vapor Pressure (psig): 35 to 55

Evaporation Rate: Slower than n-Butyl Acetate
pH: N / A

Odor Threshold (ppm): N / AV

SECTION 4 - Fire and Explosion Data

Flammability: Yes - Flammable liquid under conditions of sparks, flame, or excessive heat.

Means of Extinction: *Extinguishing Media* - Carbon dioxide, dry chemical, water spray. *Firefighting Procedures* - Closed containers may rupture due to pressure build up from extreme temperature. Use water spray to cool containers to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.

Flashpoint: 87° F (99° C) **Method Used:** PMCC **Flammable Limits - LFL:** 0.7% **UFL:** 12.0%

Autoignition Temperature: N / AV **Hazardous Combustion Products:** Carbon Monoxide, Carbon Dioxide.

Explosion Data - Sensitivity to Mechanical Impact: No **Explosion Data - Sensitivity to Static Discharge:** Primarily Vapors

SECTION 5 - Reactivity Data

Chemical Stability: Stable

Reactivity & Conditions: None

Incompatibility with Other Substances: Strong oxidizing agents.

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide

SECTION 6 - Toxicological Properties

Primary Routes of Entry: Skin Contact, Eye Contact, Inhalation

Effects of Acute Exposure to Product:

Skin Contact - Irritation.

Eye Contact - Irritation.

Inhalation - Irritation. May cause dizziness, light-headedness and / or headaches. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingestion - May be harmful or fatal if swallowed.

Effects of Chronic Exposure to Product: Dermatitis. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood.

Exposure Limits (TLV):

Aliphatic Hydrocarbon 100 ppm TWA - ACGIH 2005

Isopropanol 400 ppm TWA and 500 ppm STEL - ACGIH 2005

Irritancy: Skin, eyes, and respiratory tract.

Sensitization: N / AV

Carcinogenicity: The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive Toxicity: N / AV

Teratogenicity: N / AV

Mutagenicity: N / AV

Synergistic Products: N / AV

SECTION 7 - Preventive Measures

Personal Protective Equipment (PPE): Gloves - Yes Respirator - Yes Eye - Yes Footwear - No Clothing - No Other - No

Skin Protection - Chemical resistant gloves such as Neoprene or Nitrile rubber.

Respiratory Protection - In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator.

For concentrations above the TLV (as defined in Section 6), use a positive air supplied respirator.

Eye Protection - Safety glasses or goggles.

Engineering Controls: General ventilation to maintain exposure limits below TLV's as defined in Section 6.

Leak and Spill Procedure: Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.

Waste Disposal: Dispose of in accordance with local, state/provincial or territorial, and federal regulations. Do not incinerate closed containers.

Handling Procedures and Equipment: Do not use near heat, sparks, or open flame. Use PPE as defined in Section 7.

Storage Requirements: Do not store near heat, sparks, flame or above 120° F (49° C).

Special Shipping Information: Consumer Commodity ORM-D.

SECTION 8 - First Aid Measures

Inhalation: Remove from exposure, seek medical attention if signs/symptoms persist.

Ingestion: Do not induce vomiting. Contact physician or poison control center immediately.

Skin Contact: Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.

Eye Contact: Flush immediately with water for 15 minutes, seek medical attention if irritation persists.

SECTION 9 - Preparation Information

Prepared by: Technical Department

Telephone Number: 775-782-0100

Preparation Date: January 12, 2010

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.