



Material Safety Data Sheet

Turf Marking Paint February 2, 2007

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know.

The following material safety data sheet covers the hazardous ingredients associated with more than one color aerosol product. As per 29 CFR 1900.1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following Aervoe Industries aerosol products.

TURF MARKING PAINT

290 BLUE	292 RED
291 WHITE	293 YELLOW

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Aervoe Industries, Inc.
INFORMATION PHONE: 775-782-0100
DATE REVISED: February 2, 2007

ADDRESS: 1198 Mark Circle, Gardnerville, NV 89410
EMERGENCY PHONE: 1-800-424-9300
REASON REVISED: Updated

SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	ACGIH STEL	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
Dimethyl Ether (CAS 115-10-6)	15 - 40	N / AV	N / AV		N / AV	164,000 ppm / 4 hr (Rat-Inha)
Isopropanol (CAS 67-63-0)	3 - 7	400 ppm	400 ppm	500 ppm	4700 mg / kg (Rat-Oral)	16000 ppm / 4 hr (Rat-Inha)
*Ethylene Glycol Monobutyl Ether (CAS 111-76-2)	1 - 3	50 ppm (skin)	20 ppm (skin)		N / AV	N / AV
*Ethylene Glycol Monopropyl Ether (CAS 2807 30 9)	1 - 3	N / AV	N / AV	N / AV	N / AV	N / AV

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

NOTE: N / AP = Not Applicable N / AV = Not Available

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: N / AP	SPECIFIC GRAVITY (H20=1): 0.9 to 1.0	COEFFICIENT OF WATER/OIL DIST: N / AV
ODOR THRESHOLD: N / AV	VAPOR DENSITY: Heavier than air	SOLUBILITY IN WATER: Soluble
EVAPORATION RATE: Slower than n-Butyl Acetate	APPEARANCE AND ODOR: Opaque with alcohol odor.	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: < 0° F (-18° C) **METHOD USED:** Estimated **FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER:** 1.1% **UPPER:** 18.0%

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Water Spray

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may rupture due to pressure build up from extreme heat or fire.

SENSITIVITY TO IMPACT: Do not puncture **SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors

FLAMMABILITY: This product when tested according to 16 CFR 1500.45 (Aerosol Flame Propagation Test) is not classified as extremely flammable or flammable.

SECTION V - REACTIVITY DATA

STABILITY: Stable **CONDITIONS TO AVOID:** Open flames, sparks, electrical arcs.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - HEALTH HAZARD DATA

INHALATION: Respiratory tract irritant. May cause dizziness, light-headedness and / or headaches. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

SKIN CONTACT: Prolonged or repeated contact may cause irritation and dermatitis.

EYE CONTACT: Painful with slight to moderate irritation.

INGESTION: May be harmful or fatal if swallowed.

EFFECTS OF CHRONIC OVEREXPOSURE: Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood.

CARCINOGENICITY: The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.

TERATOGENICITY: Not established. **MUTAGENICITY:** Not established

MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE: Not established.

EMERGENCY AND FIRST AID PROCEDURES: INHALATION - Remove from exposure, seek medical attention if signs/symptoms persist.
SKIN - Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.
EYES - Flush immediately with water for 15 minutes, seek medical attention if irritation persists.
INGESTION - Do not induce vomiting. Contact physician or poison control center immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120° F. Do not store or use near heat, sparks or flame.

OTHER PRECAUTIONS: Do not smoke while using this product. Dust from sanding the dry paint films should be treated as a nuisance dust with a TLV of 15mg/cubic meter.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator. For concentrations above the TLV (as defined in Section II), use a positive air supplied respirator.

VENTILATION: General ventilation to maintain exposure limits below TLV's as defined in Section II.

PROTECTIVE GLOVES: Chemical resistant gloves such as Neoprene or Nitrile rubber.

EYE PROTECTION: Safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None

WORK / HYGIENIC PRACTICES: Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.