



Material Safety Data Sheet

Crown Waterworks Coatings Remover

5205MA

TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

This MSDS covers the following AerVOE aerosol product.

PRODUCT NAME:

HMIS CODES: H F R P
2 4 1 X



5205 Waterworks Coatings Remover

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: AerVOE Industries Inc.
INFORMATION PHONE: 775-782-0100
DATE REVISED: 02-10-09

ADDRESS: 1198 Mark Circle, Gardnerville, NV 89410
EMERGENCY PHONE: 1-800-424-9300
REASON REVISED: Revised

SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	OTHER	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
Benzyl Alcohol (CAS 100 51 6)	10 - 30	N/A	N/A		N/A	N/A
MONOETHANOLAMINE (CAS 141 43 5)	< 2	3.00 PPM	3.00 PPM		1720 mg / kg RAT (ORAL)	N/A
DIMER ESTER MIX (CAS Not listed)	1 - 5	N/A	N/A		N/A	N/A
NAPHTHA LIGHT AROMATIC (CAS 64742 95 6)	3 - 7	100 PPM	N/A		N/A	N/A
DIMETHYL ETHER PROPELLANT (CAS 115 10 6)	15 - 40	N/A	N/A		N/A	164,000 PPM; 4 hr RAT (INHA)

No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.

NOTE: N/A applies to not available or not applicable

5205MA

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: N/A
VAPOR DENSITY: Heavier than air
EVAPORATION RATE: Greater than n-Butyl Acetate

SPECIFIC GRAVITY (H2O=1): 0.96 - 1.0
SOLUBILITY IN WATER: Negligible
APPEARANCE AND ODOR: White foamed emulsion / Hydrocarbon Odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: < 0° F (-18° C)
EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Water spray may be used to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Treat as cylinders of compressed gas. Closed containers may rupture due to pressure build up from extreme heat or fire.

METHOD USED: Estimated
FLAMMABLE LIMITS - LEL: 3 - 4% **UEL:** 18%

SECTION V - REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Hydrocarbon fumes & smoke. Carbon monoxide where combustion is incomplete.
HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Hot or cold storage.

SECTION VI - HEALTH HAZARD DATA

INHALATION: Respiratory tract irritant. May cause dizziness, light-headedness and / or headaches.
SKIN CONTACT: Prolonged or repeated contact may cause defatting and / or dermatitis.
EYE CONTACT: Painful with slight to moderate irritation.
SKIN ABSORPTION: Prolonged or widespread contact may result in the absorption of potentially harmful amounts of material, with identical symptoms as ingestion.
INGESTION: Moderate to severe irritation of the gastrointestinal tract. Symptoms of exposure may include nausea, vomiting, headache, dizziness, weakness, and abdominal pain.
CARCINOGENICITY: None known
TERATOGENICITY: Not established
MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE: Not established
EMERGENCY AND FIRST AID PROCEDURES: INHALATION - Remove from exposure. Seek medical attention if signs/symptoms persist.
SPLASH - (SKIN) Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.
SPLASH - (EYES) Flush immediately with water for 15 minutes and seek medical attention if irritation persists.
INGESTION - Do NOT induce vomiting unless directed by medical personnel. Drink large quantities of milk or water and seek medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition: Flames, sparks, static electricity & electrical. Ventilate area, avoid run off into sewer by diking, and soak up with inert absorbent using non-sparking type tools.
WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 100° F (38° C). Do not store or use near heat, sparks or flame.
OTHER PRECAUTIONS: Do not get in eyes. Do not breathe vapors. Avoid skin contact. Do not take internally. Smoking while using this product must be strictly prohibited.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: Respiratory protection program should be in accordance with 29 CFR 1910.134.
VENTILATION: All application areas should be adequately ventilated in order to keep the items in SECTION II below their exposure limits.
PROTECTIVE GLOVES: Polyethylene or Neoprene gloves are recommended.
EYE PROTECTION: Safety glasses with side shields are recommended.
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Not established.
WORK / HYGIENIC PRACTICES: Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.