

Product Data Sheet

No. 31645 - 06/09

ROOF TAR & ADHESIVE REMOVER

AEROSOL

PRODUCT NUMBER: 1645

I. GENERAL DESCRIPTION

Features: Aervoe Roof Tar & Adhesive remover is a non-chlorinated tar and adhesive remover with citrus oil that also removes grease and grime from a variety of surfaces. Safe on metal and most plastics. Leaves no film or residue, and can be wiped clean with no rinsing required.

Uses: Clean tar and adhesives off of flashings, pipes, gutters, wood, and other metal. May be used to prepare certain substrates by removing heavy oils, greases, silicones and grime prior to use of any adhesives.

Application: Apply to tar and other adhesives and allow to soak in for up to 1 to 2 minutes if necessary. Wipe residue off with a cloth. On plastic, test a small area first to assure surface compatibility as this product will attack some plastics.

Directions: Align spray head with mark on valve rim to insure complete evacuation of contents. Shake can before use.

Limitations: Please refer to the Material Safety Data Sheet for specific information on material hazards, etc. Pretest substrate for compatibility.

Packaging:

Aerosol:

Cans (211x 713)

Case (12/case):

15 oz. net wt. (425 grams)

16 lbs.

18 fl. oz. (532 ml)

0.55 CF (0.016CM)



Aervoe Industries, Inc.
P.O. Box 485, Gardnerville, NV 89410



(775) 783-3100 Phone • (775) 783-5687 Fax • (800) 227-0196 Customer Service
www.aervoe.com • www.athenabrands.com • www.zynolyte.com



II. CHARACTERISTICS & PROPERTIES (1645 Roof Tar & Adhesive Remover)

Specifications: None

Appearance: Non-foaming liquid

Color: Clear

Odor: Citrus

Performance and Chemical Properties:

Weight per gallon.....	6.6 lbs/gal
Specific gravity.....	0.79
Flammability: Label marking.....	Flammable
Flash point.....	127° F (53° C)
Operating temperature range.....	30° to 110° F (-1° to 43° C)
Active ingredients by weight.....	97%
Volatile Organic Compound.....	< 97%
Evaporation Rate (Butyl Acetate = 1).....	<1
KB Value.....	.44

Base Materials:

Solvents (top two).....	Aliphatic Hydrocarbon, D-Limonene
Propellant.....	Carbon Dioxide

III. SHIPPING, STORAGE AND HEALTH

	Aerosol
IMDG number.....	1950
D.O.T. container spec.....	2Q
D.O.T. shipping description.....	Consumer Commodity
Warehouse storage level number.....	NFPA 30B Level 3
Hazardous class (CFR-49).....	ORMD
Storage temperature.....	32° to 120°F (0° to 49°C)
Shelf life.....	1 to 3 years
HMIS ratings	
Health.....	2
Fire.....	2
Reactivity.....	0

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

The statements made herein, on labels, product bulletins or by any of our employees or agents concerning this material are given for information only. Any liability whatsoever of Aervoe Industries, Inc. to the user of the product, is limited to replacement of the product or purchase price refunded.