

Product Data Sheet

No. **38377** - 06/11

ELECTRONIC COMPONENT CLEANER

AEROSOL

PRODUCT NUMBERS: 8377 - 14 OZ. NET WT. AEROSOL

I. GENERAL DESCRIPTION

Description: This product is an excellent non-flammable cleaner to flush away contaminants, film and flux on electronic components.

Benefits: Evaporates quickly, leaves no film and has a low odor. This cleaner does not have a flash point.

Applications: Use on relays, switches, contacts, circuit breakers, plugs and jacks, terminals, circuit boards, generators, electromechanical assemblies and fusible disconnects. Avoid use on certain plastics including ABS, Acrylic, Polycarbonate Polysulfones and Styrene. Test on surface before using.

Directions: For best results use at room temperature (70°F). For cleaning large areas, use the standard sprayhead. For pinpoint spray, use extension tube. Hold can 2 to 4 inches from area to be cleaned and spray in short bursts. Keep can upright while spraying. Do not use on electrical equipment or machinery while in operation.

Limitations: Please refer to the Material Safety Data Sheet for specific information on material hazards, etc. For use in manufacturing facilities.

Packaging:

Aerosol:

Cans (211x604)
12 cans/case

14 oz. net wt. (397 grams)
15 lbs. (6.8 kg)

11.2 fl. oz. (331 ml)
0.47 CF (0.013 CM)

II. CHARACTERISTICS & PROPERTIES

Specifications:

None

Appearance:

Thin, non-foaming

Color:

Colorless, transparent

Odor:

Mild

Dry Schedule:

N/A

Performance and Chemical Properties:

Weight per gallon	11.4 lbs
Specific gravity	1.4
Viscosity in centipoise	Not applicable
Flammability: Label marking	Not applicable
Flash point.....	None
Active ingredients by weight.....	60 %
Volatile Organic Compound level	100 %
Operating temperature range	40° to 110°F (4° to 43°C)
Boiling point @ 760mm Hg	90°F (32°C) Concentrate
Evaporation rate (Butyl Acetate = 1)	8.1
KB value.....	66
Dielectric strength	26 KV
Surface tension	Low
Food contact rating	N/A

Base Materials:

Solvents (top two)	1,2 - dichloroethylene, Isopropanol
Propellant system:	Tetrafluoroethane

III. SHIPPING, STORAGE AND HEALTH

IMDG number.....	UN 1950
D.O.T. container spec.....	2Q
D.O.T. shipping description	Consumer Commodity
Warehouse storage level number	NFPA 30B Level 1
Hazardous class (CFR-49).....	ORM-D
Storage temperature	32° to 120°F (0° to 49°C)
Shelf life	1 to 3 years
HMIS ratings	
Health.....	2
Fire	1
Reactivity.....	1

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

The statements made herein, on labels, product bulletins or by any of our employees or agents concerning this material are given for information only. Any liability whatsoever of Aervoe Industries, Inc. to the user of the product, is limited to replacement of the product or purchase price refunded.

NO. 38377 - 06/11